ARLO Q

DATASHEET

SURFACE APPLICATION

LED | 230V/50Hz | IP20



PRODUCT DESCRIPTION

Adjustable LED luminaire for surface-mounted application.
Epoxy-polyester lacquered aluminum body.

LIGHT SOURCE

GU10 Lamp

AVAILABLE COLOR/FINISH

1-white/ 2-black

AVAILABLE LIGHT TEMPERATURE/ COLOR

2700K/ 3000K/ 4000K

AVAILABLE DRIVER

1- HF - ON/OFF
2- DALI - Flow regulation

STANDARTS: EN 60598-1, EN 60598-2-1

TECHNICAL DRAWING



ARLO Q

LED GU10	POWER (W)	FLOW (lm)	CODE
	6	560	ARLOQ.006.LK.AED
	8	825	ARLOQ.008.LK.AED
	-	-	ARLOQ.000.LK.AED

ARLO Q - COB LED*

9	1100	ARLOQ.009.LK.AED
12	1500	ARLOQ.012.LK.AED

*cob led light with remote driver

KATOA
Everything's Lighting

Rua Dr. Manuel Ramos, 285 - Pavilhão E
4415-456 Grijó - Vila Nova de Gaia
Portugal

+351 221 110 602
ola@katoa.lighting
https://katoa.lighting/