PIK Q DATASHEET

RECESSED APPLICATION

LED | 230V/50Hz | IP54



STANDARTS: EN 60598-1, EN 60598-2-1

65° 39

TECHNICAL DRAWING



PRODUCT DESCRIPTION

LED luminaire for recessed application, with trim.
Injected aluminum body, thermo-lacquered with anti-aging corrosion additive.
Opening beam angle: 65°

LIGHT SOURCE

Driver LED, 220-240VAC -50/60Hz
CRI>80, FP>0.9, 50.000h of useful life.

AVAILABLE COLOR/FINISH

1-white/ 2-black

AVAILABLE LIGHT TEMPERATURE/ COLOR

3000K/ 4000K

AVAILABLE DIFFUSER

F - frosted

AVAILABLE DRIVER*

1- HF - ON/OFF
*remote driver



Recessed box not included

hole for negative: 41

PIK Q

	POWER (W)	FLOW (lm)	CODE
	2	96	PIKQ.002.LK.AED
Recessed box	-	-	PIK.NEG.XX.XX

KATOA Everything's Lighting

Rua Dr. Manuel Ramos, 285 - Pavilhão E
4415-456 Grijó - Vila Nova de Gaia
Portugal

+351 221 110 602
ola@katoa.lighting
https://katoa.lighting/