SPLIT DATASHEET

RECESSED APPLICATION

LED | 230V/50Hz | IP54



STANDARTS: EN 60598-1, EN 60598-2-1

C1	C2	C3	C4	C5	C6
90	125	140	160	210	230

TECHNICAL DRAWING



PRODUCT DESCRIPTION

LED luminaire for recessed application in the ceiling, with trim.
Epoxy-polyester lacquered aluminum frame.
Suitable for harsh climate environments.

LIGHT SOURCE

Driver LED, 220-240VAC-50/60Hz.
CRI>80, 35.000h of useful life.

AVAILABLE COLOR/FINISH

1-white/ 2-black/ 4-anthracite/ 6-grey

AVAILABLE LIGHT TEMPERATURE/ COLOR

3000K/ 4000K

AVAILABLE DIFFUSER

O -opaline

AVAILABLE DRIVER

1- HF - ON/OFF
2- DALI - Flow regulation
3- 1-10V - Flow regulation

SPLIT

	DIMENSIONS (mm)	POWER (W)	FLOW (lm)	CODE
C1	Ø110xH20.5	9	700	SPLIT.110.LK.AED
C2	Ø140xH20.5	11	880	SPLIT.140.LK.AED
C3	Ø155xH20.5	15	1200	SPLIT.155.LK.AED
C4	Ø180xH20.5	18	1440	SPLIT.180.LK.AED
C5	Ø230xH20.5	23	1840	SPLIT.230.LK.AED
C6	Ø254xH55	25	3100	SPLIT.254.LK.AED

KATOA
Everything is Lighting

Rua Dr. Manuel Ramos, 285 - Pavilhão E
4415-456 Grijó - Vila Nova de Gaia
Portugal

+351 221 110 602
ola@katoa.lighting
https://katoa.lighting/