POP 100 SV

DATASHEET

SUSPENDED APPLICATION

LED | 24V | IP43



STANDARDS: EN 60598-1, EN 60598-2-1

360°

Possibility of surface-mounted cablecup (default) or recessed.

TECHNICAL DRAWING



PRODUCT DESCRIPTION

LED tubular luminaire for suspended vertical application.
Body with 100mm in diameter in opal poly-carbonate. Tops in lacquered aluminum.

LIGHT SOURCE

Driver LED, 24V.

AVAILABLE COLOR/FINISH

1-white/ 2-black/ 4-anthracite/ 5-brushed/ 6-grey

AVAILABLE LIGHT TEMPERATURE/COLOR

2700K/ 3000K/ 4000K/ 6500K

AVAILABLE DIFFUSER

0 -opaline

AVAILABLE DRIVER

1- HF - ON/OFF
2- DALI- Flow regulation

AVAILABLE APPLICATION



Surface (standard)
Ø86x20mm
code: FL.SAL.86



Recessed
Ø86mm
code:FL.ENC.86



Surface-mount driver enclosure
403x36x40mm
code:FL.LIN.403.DR

POP 100 SV

DIMENSIONS (mm)	POWER (W)	FLOW (lm)	CODE
540	30	3380	POP1SV.0540.LK.AED
1040	60	6760	POP1SV.1040.LK.AED
1540	90	10140	POP1SV.1540.LK.AED
2040	120	13520	POP1SV.2040.LK.AED

Possibility of custom lines - On request

KATOA
Everything is Lighting

Rua Dr. Manuel Ramos, 285 - Pavilhão E
4415-456 Grijó - Vila Nova de Gaia
Portugal

+351 221 110 602
ola@katoa.lighting
https://katoa.lighting/