SPLIT N DATASHEET

RECESSED APPLICATION

LED | 230V/50Hz | IK03 | IP44



STANDARTS: EN 60598-1, EN 60598-2-1

C1 100 C2 150 C3 200

TECHNICAL DRAWING



PRODUCT DESCRIPTION

LED luminaire for recessed application in the ceiling, with trim.
Epoxy-polyester lacquered aluminum frame.
Suitable for harsh climate environments.

LIGHT SOURCE TRIDONIC

Driver LED, 220-240VAC-50/60Hz.
CRI>80, 50.000h of useful life.

AVAILABLE COLOR/FINISH

1-branco/ 8-RAL

AVAILABLE LIGHT TEMPERATURE/ COLOR

3000K/ 4000K/ 5500K

AVAILABLE DIFFUSER

0 -opaline

AVAILABLE DRIVER

1- HF - ON/OFF
2- DALI - Flow regulation

SPLIT N

	DIMENSIONS (mm)	POWER (W)	FLOW (lm)	CODE
C1	Ø120x27	8.8	880	SPLITN.100.LK.AED
C2	Ø170x27	13	1500	SPLITN.150.LK.AED
C3	Ø220x27	18	2160	SPLITN.200.LK.AED

KATOA Everything is Lighting

Rua Dr. Manuel Ramos, 285 - Pavilhão E
4415-456 Grijó - Vila Nova de Gaia
Portugal

+351 221 110 602
ola@katoa.lighting
https://katoa.lighting/